

## TECHNICAL DATA SHEET FINISEAL<sup>®</sup> 8204

<b>Trade name:</b>	FINISEAL <sup>®</sup> 8204
<b>Raw material:</b>	Aramide Staple yarn FINITEXT <sup>®</sup> , PTFE dispersion, lubricants
<b>Technical parameters:</b>	
Working temperature:	-100°C / +280°C
Working pressure:	
Rotary pumps	20 bar
Piston pumps	70 bar
armature	150 bar
pH:	3 – 13
V:	17 m/sec
Standard dimensions:	from 3x3 mm to 28 x 28 mm
<b>Application:</b>	<p>The structure of staple fibers and high percentage of impregnation with PTFE, determined the packing as the best product for exploitation in abrasive media. Abrasive particles incorporate in the soft structure of staple fibers, but without breaking the packing. The packing is resistant to cutting and wearing out.</p> <p>It is mainly used for sealing of pumps, agitators, shafts, valves in chemical, pharmaceutical, paper, sugar industry, metallurgy, etc.</p>
<b>Aspects on environment:</b>	During the production, exploitation or as waste it is not dangerous for environment.
<b>Health hazardous:</b>	There is not registered.

FINITEXT<sup>®</sup> is a trade mark of "FINISTRA" JSC – Russe